

Imperial Version



Doing It Right
DIR-diver.com

Minimum Deco Table

30-32% Nitrox

Rev. A

Depth
fsw
(using Air)

Depth fsw (using Air)	BT	Bottom Time						
	Max	Adjusted Maximum Bottom Time						
120 → (100)	8 17	10 15	15 10	20 5	25 0			
100 → (80)	10 25	15 20	20 15	25 10	30 5	35 0		
80 → (65)	10 40	20 30	25 25	30 20	40 10	50 0		
60 → (50)	25 60	35 50	45 40	55 30	65 20	75 10	85 0	
50 → (40)	30 130	40 120	60 100	80 80	100 60	120 40	140 20	160 0
Group	A	B	C	D	E	F	G	H

- Always do the deco stops no matter what depth or duration of your dive.
- Never ascend faster than 30 ft/min, especially the last 20 feet.
- When you must dive on air - use the air depths instead.
- This table is designed for up to four dives per day.

Buhlmann ZH-L16B
with Gradient Factors

32% ~ GF 30/85
30% ~ GF 30/90
21% ~ GF 30/90

Surface Interval		Mandatory Stops	
time	group	fsw	minutes
0:10	same	40	1
0:30	- 2 *	30	1
1:00	- 4 *	20	3
2:00	- 5 *	10	3
4:00	none		

* but no less than A